


Smart Control



C TYPE (*)

Injection Molding Machine

C Type Injection Molding Machine



- Tie-bar less (C type) design gives more space for operation. Especially suitable for the power cord and connector with wire.
- Precision vertical clamping system (parallelism/ flatness : 0.02/ 100 mm), heavy-duty tie-bars, and low-pressure mold clamping work together to greatly extend machine & mold life.
- With shuttle table > rotary table, pick and place products while molding finish, make production safe and efficient, then reduce the cost of production.
- Material injected through parting line to cavities.











Suitable For Wall Suitable For Much Safety Design Vertical Hydraulic Horizontal Clamping Thickness More Injection Capacity For Operator

Model		
INJECTION UNIT		
Screw Diameter	mm	
Injection Capacity	cm³	
Injection Pressure	kgf/cm²	
Injection Weight	oz	
	gram	
Injection Rate	cc/s.	
Screw Speed	r.p.m.	
Screw Stroke	mm	
Nozzle Stroke	mm	
Nozzle Contact Force	ton	
CLAMPING UNIT		
Clamping Force	ton	
Minimum Mold Height	mm	
Opening Stroke	mm	
Maximum Daylight	mm	
Overall Size Of Platens	mm	
Size Of ShuttleTable	mm	
Shuttle Table Stroke	mm	
Diameter Of Rotary Table	mm	
Mold Station	Station	
Ejector Force	ton	
Ejector Stroke	mm	
ELECTRICAL EQUIPMEN	IT & GENE	RAL
Power Source	v/hz	
Drive Motor	kW	
Heater	kW	
Temperature Control Zone	zone	
Hydraulic System Pressure	kgf/cm²	
Machine Dimension	m	
Machine Weight	ton	

KING'S Solution Corp.